



## Tubular Bells Pro Suspension

07.9466.11B - Matt White


Suspension luminaire to be installed on ceiling for led. phosphor led module integrated. electronic transformer 220/240V integrated.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 394                 |
| Lamp category   | LED   | Mountings      | Suspension          |
| Power (W)       | 7.4W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 98    |                |                     |

### Optical

|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Flood        |
| Beam angle (°)         | 32           |
| Beam angle C90-270 (°) | 32           |



Beam Angle: 32°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1227  | 0.58 |
| 2    | 307   | 1.16 |
| 3    | 136   | 1.73 |
| 4    | 77    | 2.31 |
| 5    | 49    | 2.89 |

Luminous flux luminaire  
394 lm (EXTREME CUT OFF)



### Electrical

|                |              |                  |         |
|----------------|--------------|------------------|---------|
| Frequency (Hz) | 50/60        | Emergency        | Without |
| Voltage (V)    | 220.00       | Insulation class | I       |
| Dimmable       | No           |                  |         |
| Driver         | Integrated   |                  |         |
| Driver type    | Non Dimmable |                  |         |

### Physical

|             |            |
|-------------|------------|
| Color       | Matt White |
| Orientation | Fixed      |
| Weight (kg) | 1.10       |

