



USO 2500 Cove Lighting

SA.1009.5D110 - Raw

Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions. See LED LED drivers.




Main specifications

| | | | |
|------------------------|------------------|--------------------|---------------------|
| Number of heads | 54 | Environment | Indoor dry location |
| Lamp category | LED | | |
| Power (W) | 194W | | |
| CRI | 90 | | |
| Mountings | Ceiling recessed | | |

Optical

| | |
|---------------------------|----------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| Optical type | Diffused light |



Beam Angle: 138°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 1065 | 5.23 |
| 2 | 266 | 10.45 |
| 3 | 118 | 15.68 |
| 4 | 67 | 20.90 |
| 5 | 43 | 26.13 |

Luminous flux luminaire
3791 lm

Electrical

| | |
|--------------------|-----------------|
| Voltage (V) | 24 |
| Dimmable | No |
| Driver | Remote excluded |
| Emergency | Without |

Physical

| | |
|----------------------------|-------|
| Color | Raw |
| Orientation | Fixed |
| Recessed depth (mm) | 210 |
| Weight (kg) | 185 |
| Length (mm) | 3000 |

Note

Delivered in two pieces.