

09.4522.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	1067
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11957	0.19
2	2989	0.39
3	1329	0.58
4	747	0.77
5	478	0.97

Luminous flux lumineuse
1067 lm

Electrical

Frequency (Hz)	50/60	Emergency Insulation class	Without II
Voltage (V)	220.00		
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		


Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.73
Tilt (°)	90
Rotation (°)	360

Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

UT Downlight No Trim Ø 57 Dali Version



Elliptical lens
08.8431.00



Flood lens
08.8432.00



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00



Installation frame NO TRIM
08.8994.30



Installation frame NO TRIM
08.8994.14



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW