


## UT Downlight No Trim Ø 57 Dali Version

■ 09.4522.30ADA - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1067
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	18W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	11
<b>Beam angle C90-270 (°)</b>	11



Beam Angle: 11°

	h(m)	E(lx)	D(m)
1	11957	0.19	
2	2989	0.39	
3	1329	0.58	
4	747	0.77	
5	478	0.97	

Luminous flux luminaire  
1067 lm

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.73
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360

### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



## UT Downlight No Trim Ø 57 Dali Version



---

Snoot shielding cone  
08.0526.BW



---

Installation frame NO TRIM  
08.8994.30



---

Installation frame NO TRIM  
08.8994.14




---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.40



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.00