

09.4527.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 932                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 18W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 43        |
| Beam angle C90-270 (°) | 43        |



Luminous flux lumineuse  
932 lm

|             |              |             |  |
|-------------|--------------|-------------|--|
| Beam Angle: | 43°          |             |  |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |  |
| 1           | 2050         | 0.79        |  |
| 2           | 512          | 1.58        |  |
| 3           | 228          | 2.37        |  |
| 4           | 128          | 3.16        |  |
| 5           | 82           | 3.95        |  |

## Electrical

|                |                 |                                       |            |
|----------------|-----------------|---------------------------------------|------------|
| Frequency (Hz) | 50/60           | <b>Emergency<br/>Insulation class</b> | Without II |
| Voltage (V)    | 220.00          |                                       |            |
| Dimmable       | Yes             |                                       |            |
| Driver         | Remote included |                                       |            |
| Driver type    | Dimmable DALI   |                                       |            |
|                | 1               |                                       |            |

## Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.73       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

UT Downlight No Trim Ø 57 Dali Version



---

Honeycomb  
08.8428.00




---

Snoot shielding cone  
08.0526.00



---

Snoot shielding cone  
08.0526.40



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00



---

Snoot shielding cone  
08.0526.BW



---

Installation frame NO TRIM  
08.8994.30



---

Installation frame NO TRIM  
08.8994.14



---

Screening crosspiece  
08.8429.00