


UT Downlight No Trim Ø 57 Non Dimmable

09.4524.30A - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	820
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	43
Beam angle C90-270 (°)	43



Beam Angle:	43°		
h(m)	E(lx)	D(m)	
1	1805	0.79	
2	451	1.58	
3	201	2.37	
4	113	3.16	
5	72	3.95	

Luminous flux luminaire
820 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.73
Tilt (°)	90
Rotation (°)	360

Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Downlight No Trim Ø 57 Non Dimmable



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00



Screening crosspiece
08.8429.00



Installation frame NO TRIM
08.8994.30



Installation frame NO TRIM
08.8994.14



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW



Elliptical lens
08.8431.00



Flood lens
08.8432.00