


## UT Downlight No Trim Ø 57 Non Dimmable

■ 09.4527.30A - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 932                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 18W   | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 43        |
| Beam angle C90-270 (°) | 43        |



Beam Angle: 43°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2050  | 0.79 |
| 2    | 512   | 1.58 |
| 3    | 228   | 2.37 |
| 4    | 128   | 3.16 |
| 5    | 82    | 3.95 |

Luminous flux luminaire  
932 lm

### Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.73       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Downlight No Trim Ø 57 Non Dimmable



---


Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00

---

Elliptical lens  
08.8431.00

---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00

---

Installation frame NO TRIM  
08.8994.30

---

Installation frame NO TRIM  
08.8994.14