

09.4923.14A - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1781                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 27W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 24        |
| Beam angle C90-270 (°) | 24        |



Luminous flux lumineuse  
1781 lm

|             |             |              |             |
|-------------|-------------|--------------|-------------|
| Beam Angle: | 24°         |              |             |
|             | <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |
| 1           | 8082        | 0.43         |             |
| 2           | 2020        | 0.86         |             |
| 3           | 898         | 1.28         |             |
| 4           | 505         | 1.71         |             |
| 5           | 323         | 2.14         |             |

## Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 36.00           | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

## Physical

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | Black      | Rotation (°) | 360 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 176        |              |     |
| Weight (kg)         | 0.94       |              |     |
| Tilt (°)            | 90         |              |     |

### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Downlight No Trim Ø 86 Non Dimmable



Screening crosspiece  
08.8411.00



Installation frame NO TRIM  
08.8995.30



Holding ring  
08.8410.00



Installation frame NO TRIM  
08.8995.14



Elliptical lens  
08.8163.68



Flood lens  
08.8175.68



Honeycomb  
08.8495.14