


## UT Downlight No Trim Ø57 Non Dimmable

09.4521.30A - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 995              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 18W   | Environment    | Indoor           |
| CCT (K)         | 3000K |                |                  |
| CRI             | 80    |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 43        |
| Beam angle C90-270 (°) | 43        |



Beam Angle: 43°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2190  | 0.79 |
| 2    | 548   | 1.58 |
| 3    | 243   | 2.37 |
| 4    | 137   | 3.16 |
| 5    | 88    | 3.95 |

Luminous flux luminaire  
995 lm

### Electrical


|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | remote included |                  |         |
| Driver type    | Electronic      |                  |         |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.73       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Downlight No Trim Ø57 Non Dimmable



Installation frame NO TRIM  
08.8994.30

Installation frame NO TRIM  
08.8994.14

Screening crosspiece  
08.8429.00



Elliptical lens  
08.8431.00

Flood lens  
08.8432.00

Honeycomb  
08.8428.00



Snoot shielding cone  
08.0526.00

Snoot shielding cone  
08.0526.40

Snoot shielding cone  
08.0526.BW