


UT Downlight No Trim Ø57 Non Dimmable

■ 09.4525.14A - Black

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1212
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	11



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	13577	0.19
2	3394	0.39
3	1509	0.58
4	849	0.77
5	543	0.97

Luminous flux luminaire
1212 lm

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	remote included		
Driver type	Electronic		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.73
Tilt (°)	90
Rotation (°)	360

Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Downlight No Trim Ø57 Non Dimmable



Installation frame NO TRIM
08.8994.30

Installation frame NO TRIM
08.8994.14

Screening crosspiece
08.8429.00



Elliptical lens
08.8431.00

Flood lens
08.8432.00

Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00

Snoot shielding cone
08.0526.40

Snoot shielding cone
08.0526.BW