



UT Downlight No Trim Ø86 Dali Version

09.4922.30ADA - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.



Certification / Marking




Main specifications

Number of heads	1	Net lumen (lm)	1867
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle: 12°			
	h(m)	E(lx)	D(m)
1	24053	0.21	
2	6013	0.41	
3	2673	0.62	
4	1503	0.82	
5	962	1.03	

Luminous flux luminaire
1867 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	Yes		
Driver	remote included		
Driver type	Electronic dimnable DALI		

Physical

Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Downlight No Trim Ø86 Dali Version



Elliptical lens
08.8163.68



Flood lens
08.8175.68



Honeycomb
08.8495.14



Holding ring
08.8410.00



Screening crosspiece
08.8411.00



Installation frame NO TRIM
08.8995.30



Installation frame NO TRIM
08.8995.14