


## UT Downlight No Trim Ø86 Dali Version

■ 09.4925.14ADA - Black

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 1945             |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 27W   | Environment    | Indoor           |
| CCT (K)         | 4000K |                |                  |
| CRI             | 90    |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 12        |
| Beam angle C90-270 (°) | 12        |



Beam Angle: 12°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 25058 | 0.21 |
| 2    | 6265  | 0.41 |
| 3    | 2784  | 0.62 |
| 4    | 1566  | 0.82 |
| 5    | 1002  | 1.03 |

Luminous flux luminaire  
1945 lm


### Electrical

|                |                             |                  |         |
|----------------|-----------------------------|------------------|---------|
| Frequency (Hz) | 50/60                       | Emergency        | Without |
| Voltage (V)    | 36.00                       | Insulation class | II      |
| Dimmable       | Yes                         |                  |         |
| Driver         | remote included             |                  |         |
| Driver type    | Electronic<br>dimmable DALI |                  |         |

### Physical

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | Black      | Rotation (°) | 360 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 176        |              |     |
| Weight (kg)         | 0.94       |              |     |
| Tilt (°)            | 90         |              |     |

### Certification / Marking



### Note

Pre-installation frame must be ordered separately. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Downlight No Trim Ø86 Dali Version



---

Elliptical lens  
08.8163.68



---

Flood lens  
08.8175.68



---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00



---

Installation frame NO TRIM  
08.8995.30



---

Installation frame NO TRIM  
08.8995.14