

09.4517.30A - White


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	918
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	21
Beam angle C90-270 (°)	21



Luminous flux luminaire
918 lm

Beam Angle:	21°	
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	5149	0.36
2	1287	0.72
3	572	1.09
4	322	1.45
5	206	1.81

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.73
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.


UT Downlight Trim Ø 57 Non Dimmable



Flood lens
08.8432.00

Honeycomb
08.8428.00

Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.40

Screening crosspiece
08.8429.00

Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.BW