



UT Downlight Trim Ø 86 Dali Version

09.4910.30ADA - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2259
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle:	12°		
h(m)	E(lx)	D(m)	
1	29106	0.21	
2	7277	0.41	
3	3234	0.62	
4	1819	0.82	
5	1164	1.03	

Luminous flux luminaire
2259 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.


UT Downlight Trim Ø 86 Dali Version



Screening crosspiece
08.8411.00



Elliptical lens
08.8163.68



Holding ring
08.8410.00



Flood lens
08.8175.68



Honeycomb
08.8495.14