

UT Downlight Trim Ø 86 Dali Version

■ 09.4911.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2155 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 27W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|-----------|
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 24 |
| Beam angle C90-270 (°) | 24 |



Beam Angle: 24°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 9780 | 0.43 |
| 2 | 2445 | 0.86 |
| 3 | 1087 | 1.28 |
| 4 | 611 | 1.71 |
| 5 | 391 | 2.14 |

Luminous flux luminaire
2155 lm

Electrical



| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 36.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|---------------------|------------|--------------|-----|
| Color | Black | Rotation (°) | 360 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 176 | | |
| Weight (kg) | 0.94 | | |
| Tilt (°) | 90 | | |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Downlight Trim Ø 86 Dali Version



Flood lens
08.8175.68



Honeycomb
08.8495.14



Holding ring
08.8410.00



Screening crosspiece
08.8411.00



Elliptical lens
08.8163.68