

UT Downlight Trim Ø57 Dali Version

09.4514.30ADA - White


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	808
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 21°

h(m)	E(lx)	D(m)
1	4535	0.36
2	1134	0.72
3	504	1.09
4	283	1.45
5	181	1.81

Luminous flux luminaire
808 lm

Electrical



Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	remote included		
Driver type	Electronic dimmable DALI		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.73
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Downlight Trim Ø57 Dali Version



Screening crosspiece
08.8429.00

Elliptical lens
08.8431.00

Flood lens
08.8432.00



Honeycomb
08.8428.00

Snout shielding cone
08.0526.00

Snout shielding cone
08.0526.40



Snout shielding cone
08.0526.BW