

## UT Downlight Trim Ø86 Dali Version

■ 09.4910.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

## Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 2259             |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 27W   | Environment    | Indoor           |
| CCT (K)         | 3000K |                |                  |
| CRI             | 80    |                |                  |

## Optical

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 12        |
| Beam angle C90-270 (°) | 12        |



Beam Angle: 12°

h(m) E(lx) D(m)

1 29106 0.21

2 7277 0.41

3 3234 0.62

4 1819 0.82

5 1164 1.03

Luminous flux luminaire  
2259 lm

## Electrical


|                |                             |                  |         |
|----------------|-----------------------------|------------------|---------|
| Frequency (Hz) | 50/60                       | Emergency        | Without |
| Voltage (V)    | 36.00                       | Insulation class | II      |
| Dimmable       | Yes                         |                  |         |
| Driver         | remote included             |                  |         |
| Driver type    | Electronic<br>dimmable DALI |                  |         |

## Physical


|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | Black      | Rotation (°) | 360 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 176        |              |     |
| Weight (kg)         | 0.94       |              |     |
| Tilt (°)            | 90         |              |     |

## Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## Certification / Marking



UT Downlight Trim Ø86 Dali Version



---

Elliptical lens  
08.8163.68

---

Flood lens  
08.8175.68

---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00

---

Screening crosspiece  
08.8411.00