

UT Downlight Trim Ø86 Dali Version

■ 09.4912.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	2053
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	5741	0.67
2	1435	1.34
3	638	2.01
4	359	2.69
5	230	3.36

Luminous flux luminaire
2053 lm

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	Yes		
Driver	remote included		
Driver type	Electronic dimmable DALI		

Physical


Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



Certification / Marking



UT Downlight Trim Ø86 Dali Version



Elliptical lens
08.8163.68

Flood lens
08.8175.68

Honeycomb
08.8495.14



Holding ring
08.8410.00

Screening crosspiece
08.8411.00