

## UT Downlight Trim Ø86 Dali Version

■ 09.4913.14ADA - Black


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

## Main specifications

Number of heads	1	Net lumen (lm)	1867
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

## Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	24053	0.21
2	6013	0.41
3	2673	0.62
4	1503	0.82
5	962	1.03

Luminous flux luminaire  
1867 lm

## Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	Yes		
Driver	remote included		
Driver type	Electronic dimmable DALI		

## Physical


Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

## Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## Certification / Marking



UT Downlight Trim Ø86 Dali Version



---

Elliptical lens  
08.8163.68

---

Flood lens  
08.8175.68

---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00

---

Screening crosspiece  
08.8411.00