



## UT Downlight Trim Ø86 Dali Version

■ 09.4915.14ADA - Black

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.



### Certification / Marking




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1697
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	27W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	37
<b>Beam angle C90-270 (°)</b>	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	4745	0.67
2	1186	1.34
3	527	2.01
4	297	2.69
5	190	3.36

Luminous flux luminaire  
1697 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	36.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	remote included		
<b>Driver type</b>	Electronic dimnable DALI		

### Physical

<b>Color</b>	Black	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	176		
<b>Weight (kg)</b>	0.94		
<b>Tilt (°)</b>	90		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

## UT Downlight Trim Ø86 Dali Version



---

Elliptical lens  
08.8163.68



---

Flood lens  
08.8175.68



---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00