


UT Downlight Trim Ø86 Dali Version

09.4918.30ADA - White

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 1768 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 27W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 37 |
| Beam angle C90-270 (°) | 37 |



Beam Angle: 37°

| | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 4943 | 0.67 | |
| 2 | 1236 | 1.34 | |
| 3 | 549 | 2.01 | |
| 4 | 309 | 2.69 | |
| 5 | 198 | 3.36 | |

Luminous flux luminaire
1768 lm

Electrical

| | | | |
|-----------------------|-----------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 36.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | remote included | | |
| Driver type | Electronic dimnable DALI | | |


Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | White | Rotation (°) | 360 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 176 | | |
| Weight (kg) | 0.94 | | |
| Tilt (°) | 90 | | |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Certification / Marking



UT Downlight Trim Ø86 Dali Version



Elliptical lens
08.8163.68



Flood lens
08.8175.68



Honeycomb
08.8495.14



Holding ring
08.8410.00



Screening crosspiece
08.8411.00