


## UT Downlight Trim Ø86 Non Dimmable

■ 09.4911.14A - Black

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

Number of heads	1	Net lumen (lm)	2155
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

### Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24



Beam Angle: 24°

	h(m)	E(lx)	D(m)
1	9780	0.43	
2	2445	0.86	
3	1087	1.28	
4	611	1.71	
5	391	2.14	

Luminous flux luminaire  
2155 lm


### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	No		
Driver	remote included		
Driver type	Electronic		

### Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

### Certification / Marking



### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Downlight Trim Ø86 Non Dimmable



---

Elliptical lens  
08.8163.68

---

Flood lens  
08.8175.68

---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00

---

Screening crosspiece  
08.8411.00