

UT Downlight Trim Ø86 Non Dimmable

09.4916.30A - White


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	1945
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	25058	0.21
2	6265	0.41
3	2784	0.62
4	1566	0.82
5	1002	1.03

Luminous flux luminaire
1945 lm

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	No		
Driver	remote included		
Driver type	Electronic		

Physical


Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



Certification / Marking



UT Downlight Trim Ø86 Non Dimmable



Elliptical lens
08.8163.68

Flood lens
08.8175.68

Honeycomb
08.8495.14



Holding ring
08.8410.00

Screening crosspiece
08.8411.00