

## UT Downlight Trim Ø86 Non Dimmable

09.4917.30A - White


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

## Main specifications

Number of heads	1	Net lumen (lm)	1855
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	27W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

## Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24



Beam Angle: 24°

h(m)	E(lx)	D(m)
1	8420	0.43
2	2105	0.86
3	936	1.28
4	526	1.71
5	337	2.14

Luminous flux luminaire  
1855 lm

## Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	II
Dimmable	No		
Driver	remote included		
Driver type	Electronic		

## Physical


Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	176		
Weight (kg)	0.94		
Tilt (°)	90		

## Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## Certification / Marking



UT Downlight Trim Ø86 Non Dimmable



---

Elliptical lens  
08.8163.68

---

Flood lens  
08.8175.68

---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00

---

Screening crosspiece  
08.8411.00