


## UT Pro 150 GA-69 On Board Dimmer

■ 09.7271.14A - Black

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included.




### Main specifications

Number of heads	1	Net lumen (lm)	1951
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle:	16°		
	h(m)	E(lx)	D(m)
1	18057	0.28	
2	4514	0.56	
3	2006	0.84	
4	1129	1.12	
5	722	1.40	

Luminous flux luminaire  
1951 lm

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Physical

Color	Black	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

### Certification / Marking



## UT Pro 150 GA-69 On Board Dimmer



---

Snoot shielding cone  
08.0526.00



---

Honeycomb  
08.8428.00



---

Screening crosspiece  
08.8429.00



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00