



UT Pro 150 GA-69 On Board Dimmer

■ 09.7272.14A - Black


Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included.

Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	2198
Power (W)	23.5W	Mountings	Track
System power (W)	23.5	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28



Beam Angle: 28°

h(m) E(lx) D(m)

1 10158 0.50

2 2540 1.00

3 1129 1.50

4 635 2.00

5 406 2.50

Luminous flux luminaire
2198 lm

Electrical




Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	Black	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.




UT Pro 150 GA-69 On Board Dimmer



Flood lens
08.8432.00

Snoot shielding cone
08.0526.00

Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.BW

Elliptical lens
08.8431.00

Snoot shielding cone
08.0526.40



Honeycomb
08.8428.00