


## UT Pro 150 GA-69 On Board Dimmer

09.7274.40A - White

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.




### Main specifications

Number of heads	1	Net lumen (lm)	2224
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40



Beam Angle:	40°		
	h(m)	E(lx)	D(m)
1	5634	0.73	
2	1408	1.46	
3	626	2.18	
4	352	2.91	
5	225	3.64	

Luminous flux luminaire  
2224 lm

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Certification / Marking



### Physical

Color	White	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

## UT Pro 150 GA-69 On Board Dimmer



---

Snoot shielding cone  
08.0526.00




---

Honeycomb  
08.8428.00



---

Screening crosspiece  
08.8429.00



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00