



## UT Pro 150 GA-69 On Board Dimmer

■ 09.7276.40A - White


Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1872
Power (W)	23.5W	Mountings	Track
System power (W)	23.5	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

	h(m)	E(lx)	D(m)
1	17329	0.28	
2	4332	0.56	
3	1925	0.84	
4	1083	1.12	
5	693	1.40	

Luminous flux luminaire  
1872 lm

### Electrical



Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

### Physical


Color	White	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 150 GA-69 On Board Dimmer



Elliptical lens  
08.8431.00

Snoot shielding cone  
08.0526.00

Flood lens  
08.8432.00



Snoot shielding cone  
08.0526.BW

Honeycomb  
08.8428.00

Screening crosspiece  
08.8429.00



Snoot shielding cone  
08.0526.40