


## UT Pro 150 GA-69 On Board Dimmer All White

09.7278.40A78 - White/White

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1838
Power (W)	23.5W	Mountings	Track
System power (W)	23.5	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40



Beam Angle: 40°

h(m)	E(lx)	D(m)
1	4656	0.73
2	1164	1.46
3	517	2.18
4	291	2.91
5	186	3.64

Luminous flux luminaire  
1838 lm

### Electrical


Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

### Physical

Color	White/White
Orientation	Adjustable
Weight (kg)	0.56
Rotation (°)	360
Spot diameter (mm)	57

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 150 GA-69 On Board Dimmer All White



---


Snoot shielding cone  
08.0526.BW

---

Snoot shielding cone  
08.0526.00

---

Honeycomb  
08.8428.00



---

Elliptical lens  
08.8431.00

---

Screening crosspiece  
08.8429.00

---

Snoot shielding cone  
08.0526.40



---

Flood lens  
08.8432.00