



## UT Pro 150 On Board Dimmer

■ 09.7211.40A - White


Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

Number of heads	1	Net lumen (lm)	1951
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

	h(m)	E(lx)	D(m)
1	18057	0.28	
2	4514	0.56	
3	2006	0.84	
4	1129	1.12	
5	722	1.40	

Luminous flux luminaire  
1951 lm



### Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Physical

Color	White	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 150 On Board Dimmer



Honeycomb  
08.8428.00



Elliptical lens  
08.8431.00



Snoot shielding cone  
08.0526.00



Screening crosspiece  
08.8429.00



Snoot shielding cone  
08.0526.40



Flood lens  
08.8432.00



Snoot shielding cone  
08.0526.BW