

## UT Pro 150 On Board Dimmer

09.7215.40A - White




Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1915
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	23.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	40
<b>Beam angle C90-270 (°)</b>	40



<b>Beam Angle:</b>	40°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	4851	0.73	
2	1213	1.46	
3	539	2.18	
4	303	2.91	
5	194	3.64	

Luminous flux luminaire  
1915 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	57
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.56		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## UT Pro 150 On Board Dimmer



---

Snoot shielding cone  
08.0526.40



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.BW



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.00



---

Elliptical lens  
08.8431.00