



UT Pro 150 On Board Dimmer

■ 09.7217.14A - Black


Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.

Main specifications

Number of heads	1	Net lumen (lm)	1816
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical



Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28



Beam Angle: 28°

	h(m)	E(lx)	D(m)
1	0.50	8395	
2	1.00	2099	
3	1.50	933	
4	2.00	525	
5	2.50	336	

Luminous flux luminaire
1816 lm



Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	Black	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.56		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 150 On Board Dimmer



Snoot shielding cone
08.0526.00



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.40



Honeycomb
08.8428.00



Flood lens
08.8432.00



Snoot shielding cone
08.0526.BW



Elliptical lens
08.8431.00