


UT Pro 175 GA-69 On Board Dimmer

■ 09.7310.14 - Black

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included.




Main specifications

Number of heads	1	Net lumen (lm)	3664
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle:	12°		
h(m)	E(lx)	D(m)	
1	41811	0.21	
2	10453	0.41	
3	4646	0.62	
4	2613	0.83	
5	1672	1.03	

Luminous flux luminaire
3664 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	Black	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.25		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 175 GA-69 On Board Dimmer



Honeycomb
08.9107.00



Screening Crosspiece
08.9108.00



Elliptical Lens
08.9109.00



Flood Lens
08.9110.00



Snoot Shielding Cone
08.9111.00