



## UT Pro 175 GA-69 On Board Dimmer

09.7310.40 - White


Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	3664
Power (W)	35.3W	Mountings	Track
System power (W)	35.3	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle: 12°

h(m) E(lx) D(m)

1 41811 0.21

2 10453 0.41

3 4646 0.62

4 2613 0.83

5 1672 1.03

Luminous flux luminaire  
3664 lm

### Electrical



Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220-240V	Emergency	Without
Current (mA)	940	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

### Physical

Color	White	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	0.98		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 175 GA-69 On Board Dimmer



---

Honeycomb  
08.9107.00

---

Snoot Shielding Cone  
08.9111.00

---

Screening Crosspiece  
08.9108.00



---

Elliptical Lens  
08.9109.00

---

Flood Lens  
08.9110.00