



UT Pro 175 GA-69 On Board Dimmer

09.7317.40 - White

Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.


Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 2644 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 35.3W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |



Optical


| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 37 |
| Beam angle C90-270 (°) | 37 |



Beam Angle: 37°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 7131 | 0.66 |
| 2 | 1783 | 1.32 |
| 3 | 792 | 1.98 |
| 4 | 446 | 2.65 |
| 5 | 285 | 3.31 |

Luminous flux luminaire
2644 lm



Electrical

| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmer on board | | |

Physical

| | | | |
|--------------|------------|--------------------|----|
| Color | White | Spot diameter (mm) | 75 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.25 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro 175 GA-69 On Board Dimmer



Honeycomb
08.9107.00



Screening Crosspiece
08.9108.00



Elliptical Lens
08.9109.00



Flood Lens
08.9110.00



Snoot Shielding Cone
08.9111.00