


UT Pro 175 Lens GA-69 On Board Dimmer

■ 09.7373.14 - Black

Spotlight to be installed in standard 3-phase track with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-270V power supply integrated.




Main specifications

Number of heads	1	Net lumen (lm)	3468
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle:	56°		
	h(m)	E(lx)	D(m)
1	4649	1.07	
2	1162	2.14	
3	517	3.21	
4	291	4.29	
5	186	5.36	

Luminous flux luminaire
3468 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	Black	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.14		
Tilt (°)	90		
Rotation (°)	360		

Certification / Marking

