



UT Pro 175 Lens GA-69 On Board Dimmer

■ 09.7375.14 - Black


Spotlight to be installed in standard 3-phase track with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-270V power supply integrated.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	2986
Power (W)	35.3W	Mountings	Track
System power (W)	35.3	Environment	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle: 56°

	h(m)	E(lx)	D(m)
1	4003	1.07	
2	1001	2.14	
3	445	3.21	
4	250	4.29	
5	160	5.36	

Luminous flux luminaire
2986 lm

Electrical

Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220-240V	Emergency	Without
Current (mA)	940	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	Black	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.14		
Tilt (°)	90		
Rotation (°)	360		

