

UT Pro 175 Lens GA-69 On Board Dimmer

09.7375.40 - White

Spotlight to be installed in standard 3-phase track with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-270V power supply integrated. .40 versions come with the track adapter, the arm and the rear of the head in black.




Main specifications

Number of heads	1	Net lumen (lm)	2986
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle:	56°		
h(m)	E(lx)	D(m)	
1	4003	1.07	
2	1001	2.14	
3	445	3.21	
4	250	4.29	
5	160	5.36	

Luminous flux luminaire
2986 lm



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	White	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.14		
Tilt (°)	90		
Rotation (°)	360		

