



UT Pro 175 Lens On Board Dimmer

09.7371.40 - White


Spotlight to be installed in Tracking Power profile with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-277V power supply integrated. .40 versions come with the track adapter, the arm and the rear of the head in black.

Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 2866 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 35.3W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |


Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Beam angle (°) | 56 |
| Beam angle C90-270 (°) | 56 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 56° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 3841 | 1.07 | |
| 2 | 960 | 2.14 | |
| 3 | 427 | 3.21 | |
| 4 | 240 | 4.29 | |
| 5 | 154 | 5.36 | |

Luminous flux luminaire
2866 lm



Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmer on board | | |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | White | Spot diameter (mm) | 75 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.14 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

