


## UT Pro 175 Lens On Board Dimmer All White

09.7371.40.78 - White/White

Spotlight to be installed in Tracking Power profile with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-277V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Spotlight to be installed in Tracking Power profile with LED light source. Includes adjustable lens allowing opening angle calibration from 13° to 56°. 120-277V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2866
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	35.3W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Beam angle (°)</b>	56
<b>Beam angle C90-270 (°)</b>	56



<b>Beam Angle:</b>	56°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	3841	1.07	
2	960	2.14	
3	427	3.21	
4	240	4.29	
5	154	5.36	

Luminous flux luminaire  
2866 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		

### Physical

<b>Color</b>	White/White	<b>Spot diameter (mm)</b>	75
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.14		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		