

## UT Pro 175 On Board Dimmer

### ■ 09.7302.14 - Black

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.


Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.

### Main specifications

Number of heads	1	Net lumen (lm)	3245
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12°
Beam angle C90-270 (°)	12°



Luminous flux luminaire  
3245 lm

Beam Angle: 12°

	h(m)	E(lx)	D(m)
1	37034	0.21	
2	9258	0.41	
3	4115	0.62	
4	2315	0.83	
5	1481	1.03	

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Physical

Color	Black	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.25		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Pro 175 On Board Dimmer



---

Elliptical Lens  
08.9109.00

---

Snoot Shielding Cone  
08.9111.00

---

Honeycomb  
08.9107.00



---

Flood Lens  
08.9110.00

---

Screening Crosspiece  
08.9108.00