

## UT Pro 175 On Board Dimmer

■ 09.7304.14 - Black

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.


Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2895
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	35.3W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	25
<b>Beam angle C90-270 (°)</b>	25



<b>Beam Angle:</b>	25°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	14037	0.44	
2	3509	0.88	
3	1560	1.32	
4	877	1.76	
5	561	2.20	

Luminous flux luminaire  
2895 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		

### Physical

<b>Color</b>	Black	<b>Spot diameter (mm)</b>	75
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.25		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

## UT Pro 175 On Board Dimmer



---

Screening Crosspiece  
08.9108.00



---

Honeycomb  
08.9107.00



---

Flood Lens  
08.9110.00



---

Snoot Shielding Cone  
08.9111.00



---

Elliptical Lens  
08.9109.00