


## UT Pro 175 On Board Dimmer

09.7307.40 - White

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. .40 versions come with the track adapter, the arm and the rear of the head in black.




### Main specifications

Number of heads	1	Net lumen (lm)	2644
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	7131	0.66
2	1783	1.32
3	792	1.98
4	446	2.65
5	285	3.31

Luminous flux luminaire  
2644 lm

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

### Physical

Color	White	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.25		
Tilt (°)	90		
Rotation (°)	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

### Certification / Marking



## UT Pro 175 On Board Dimmer



---

Honeycomb  
08.9107.00



---

Screening Crosspiece  
08.9108.00



---

Elliptical Lens  
08.9109.00



---

Flood Lens  
08.9110.00



---

Snoot Shielding Cone  
08.9111.00