


UT Pro 175 On Board Dimmer All White

09.7300.40.78 - White/White

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 3664 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 35.3W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 12 |
| Beam angle C90-270 (°) | 12 |



| | |
|-------------|------------|
| Beam Angle: | 12° |
| h(m) | E(lx) D(m) |
| 1 | 41811 0.21 |
| 2 | 10453 0.41 |
| 3 | 4646 0.62 |
| 4 | 2613 0.83 |
| 5 | 1672 1.03 |

Luminous flux luminaire
3664 lm

Electrical

| | | | |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmer on board | | |

Physical

| | | | |
|--------------|-------------|--------------------|----|
| Color | White/White | Spot diameter (mm) | 75 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.25 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Certification / Marking



UT Pro 175 On Board Dimmer All White



Honeycomb
08.9107.00



Screening Crosspiece
08.9108.00



Elliptical Lens
08.9109.00



Flood Lens
08.9110.00



Snoot Shielding Cone
08.9111.00