


## UT Pro 175 On Board Dimmer All White

09.7302.40.78 - White/White

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	3245
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	35.3W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	12
<b>Beam angle C90-270 (°)</b>	12



Beam Angle: 12°

	h(m)	E(lx)	D(m)
1	37034	0.21	
2	9258	0.41	
3	4115	0.62	
4	2315	0.83	
5	1481	1.03	

Luminous flux luminaire  
3245 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		

### Physical

<b>Color</b>	White/White	<b>Spot diameter (mm)</b>	75
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.25		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

## UT Pro 175 On Board Dimmer All White



---

Flood Lens  
08.9110.00



---

Screening Crosspiece  
08.9108.00



---

Honeycomb  
08.9107.00



---

Snoot Shielding Cone  
08.9111.00



---

Elliptical Lens  
08.9109.00