



UT Pro 175 On Board Dimmer All White

09.7305.40.78 - White/White

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




Main specifications

Number of heads	1	Net lumen (lm)	3221
Lamp category	LED	Mountings	Track
Power (W)	35.3W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle:	25°		
	h(m)	E(lx)	D(m)
1	15618	0.44	
2	3904	0.88	
3	1735	1.32	
4	976	1.76	
5	625	2.20	

Luminous flux luminaire
3221 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	White/White	Spot diameter (mm)	75
Orientation	Adjustable		
Weight (kg)	1.25		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Pro 175 On Board Dimmer All White



Honeycomb
08.9107.00



Elliptical Lens
08.9109.00



Flood Lens
08.9110.00



Snoot Shielding Cone
08.9111.00



Screening Crosspiece
08.9108.00