



## UT Pro Surface 150 On Board Dimmer Included

■ 09.7295.40A - White


LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1915                |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 23.5W | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 40        |
| Beam angle C90-270 (°) | 40        |



Beam Angle: 40°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 4851  | 0.73 |
| 2    | 1213  | 1.46 |
| 3    | 539   | 2.18 |
| 4    | 303   | 2.91 |
| 5    | 194   | 3.64 |

Luminous flux luminaire  
1915 lm



### Electrical


|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | Yes             |                  |         |
| Driver         | Integrated      |                  |         |
| Driver type    | Dimmer on board |                  |         |

### Physical


|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.52       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro Surface 150 On Board Dimmer Included



---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW

---

Honeycomb  
08.8428.00



---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00

---

Snoot shielding cone  
08.0526.00