


UT Pro Surface 150 On Board Dimmer Included

09.7296.40A - White

LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.




Main specifications

Number of heads	1	Net lumen (lm)	1872
Lamp category	LED	Mountings	Ceiling surface
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle:	16°		
	h(m)	E(lx)	D(m)
1	17329	0.28	
2	4332	0.56	
3	1925	0.84	
4	1083	1.12	
5	693	1.40	

Luminous flux luminaire
1872 lm

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.52
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



UT Pro Surface 150 On Board Dimmer Included



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.00



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.BW



Flood lens
08.8432.00