



UT Pro Surface 175 On Board Dimmer Included

09.7325.40 - White

LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|-----------------|
| Number of heads | 1 | Net lumen (lm) | 3221 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 35.3W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |



Beam Angle: 25°

| | h(m) | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 15618 | 0.44 | |
| 2 | 3904 | 0.88 | |
| 3 | 1735 | 1.32 | |
| 4 | 976 | 1.76 | |
| 5 | 625 | 2.20 | |

Luminous flux luminaire
3221 lm

Electrical

| | | | |
|-----------------------|------------|-------------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Voltage (V) | 37.60 | | |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Emergency | Without | | |

Physical

| | |
|---------------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 1.25 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Pro Surface 175 On Board Dimmer Included



Honeycomb
08.9107.00



Screening Crosspiece
08.9108.00



Elliptical Lens
08.9109.00



Flood Lens
08.9110.00



Snoot Shielding Cone
08.9111.00