

UT Pro Surface 175 On Board Dimmer Included

■ 09.7328.40 - White


LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.

Main specifications

Number of heads	1	Net lumen (lm)	2941
Lamp category	LED	Mountings	Ceiling surface
Power (W)	35.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	7934	0.66
2	1983	1.32
3	882	1.98
4	496	2.65
5	317	3.31

Luminous flux luminaire
2941 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.25
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

UT Pro Surface 175 On Board Dimmer Included



Screening Crosspiece
08.9108.00



Elliptical Lens
08.9109.00



Honeycomb
08.9107.00



Snoot Shielding Cone
08.9111.00



Flood Lens
08.9110.00